

C class	Product Information GHC625BK	
	MODEL	GHC625BK
	Energy efficiency classes of domestic range hoods (A-G)	C
	Annual Energy Consumption - AEC hood (kWh/a)	31.6
	Fluid Dynamic Efficiency classes for domestic range hoods (A-G)	E
	Lighting Efficiency classes (A-G)	C
	The Grease Filtering Efficiency classes (A-G)	C
	Sound power level L WA - (dB)	65
	Time increase factor - f	1.6
	Fluid Dynamic Efficiency - FDE hood	10.1
	Energy Efficiency Index - EEI hood	71
	Measured air flow rate at best efficiency point - Q BEP (m ³ /h)	111
	Measured air pressure at best efficiency point P BEP (Pa)	160.8
	Measured electric power input at best efficiency point - W BEP (W)	49.1
	Nominal power of the lighting system - W L (W)	4
	Average illumination of the lighting system on the cooking surface - E middle (lux)	72
	Lighting Efficiency LE hood - (lux/Watt)	18
	Grease Filtering Efficiency GFE hood - (%)	78
	Minimum airflow (Q min)	150
	Maximum air flow - Q max (m ³ /h)	230
	Airflow -boost (Q boost)	-
	Minimum sound power level L WA - (dB)	45dB
	Maximum sound power level L WA - (dB)	65dB
	Sound power level-boost L WA - (dB)	-
	Measured power consumption off mode P o (W)	0
	Measured power consumption in standby mode - P s (W)	0
Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "		