

A++ class Product Information GHB972IX	
MODEL	GHB972IX
Energy efficiency classes of domestic range hoods (A-G)	A++
Annual Energy Consumption - AEC hood (kWh/a)	16
Fluid Dynamic Efficiency classes for domestic range hoods (A-G)	A
Lighting Efficiency classes (A-G)	A
The Grease Filtering Efficiency classes (A-G)	C
Sound power level L WA - (dB)	64
Time increase factor - f	0,7
Fluid Dynamic Efficiency - FDE hood	35,9
Energy Efficiency Index - EEI hood	34,6
Measured air flow rate at best efficiency point - Q BEP (m <sup>3</sup> /h)	252,9
Measured air pressure at best efficiency point P BEP (Pa)	255
Measured electric power input at best efficiency point - W BEP (W)	49,9
Nominal power of the lighting system - W L (W)	3,7
Average illumination of the lighting system on the cooking surface - E middle (lux)	112
Lighting Efficiency LE hood - (lux/Watt)	30,3
Grease Filtering Efficiency GFE hood - (%)	78,1
Minimum airflow (Q min )	202
Maximum air flow - Q max (m <sup>3</sup> /h)	600
Airflow -boost (Q boost )	-
Minimum sound power level L WA - (dB)	51
Maximum sound power level L WA - (dB)	64
Sound power level-boost L WA - (dB) Measured	-
power consumption off mode P o (W)	0,31
Measured power consumption in standby mode - P s (W)	-
Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "	